

## Professional Stereo Power Amplifier Two Channel

SP-CA300, SP-CA400, SP-CA600, SP-CA800, SP-CA1000, SP-CA1300, SP-CA1500



### Description:

#### Powerful. Reliable. Affordable.

According to the professional HI-FI (high fidelity) level design, the whole machine layout is well understood, safe and secure, concise and beautiful. Choosing Motorola seal pipe to expand outflow, careful selection and matching of components, precise production. Small output noise, big power, wide dynamic range, clear subordinate, wide sound field, clear and transparent sound, the timbre is pure and exquisite, the bass strong and thick. It has good electromagnetic compatibility, anti-vibration and anti-fall, full-function intelligent protection, and is suitable for high-grade speakers for various purposes. Mainly applicable to KTV, nightclubs, bars, outdoor performances and other high-end places.

#### Features:

- Professional stereo 2 channels power amplifier.
- Separate speaker outputs 8Ω, 4Ω.
- Each channel with LED indicator status: Signals, Dctive, Clip/Liniting.
- Perfect protection circuits and excellent sound quality.

**Specification:**

<b>Technical Parameter</b>							
Model/Power (1 KHz 5%THD)	SP-CA300	SP-CA400	SP-CA600	SP-CA800	SP-CA1000	SP-CA1300	SP-CA1500
8 Ohms Stereo	300W*2	400W*2	600W*2	800W*2	1000W*2	1300W*2	1500W*2
4 Ohms Stereo	450W*2	600W*2	900W*2	1200W*2	1500W*2	1950W*2	2250W*2
Frequency Response	20Hz-20kHz						
THD+N	≤0.01% Rated Power @ 8 Ω hms 1kHz						
Slew Ratio	30v/us						
Damping Factor	≥500:1						
Input Sensitivity	0.775V, 26dB, 32dB						
Input Impedance(rated)	10k/20k Ω, unbalanced or balanced						
S/N Ratio	>100dB						
Lep Indicator	Signals, Dctive, Clip/Liniting						
Main Power Supply	AC220V-240V / 50Hz-60Hz						
Supply Power	900W	1200W	1800W	2400W	3000W	3900W	4400W
Net Weight	16kg	17kg	22kg	30kg	33kg	37kg	39kg
Dimensions(mm)	600Dx482Wx132H						