## Two Zone PA Mixer Amplifier Independent Volume Control SP-MT60(60W) SP-MT120(120W) SP-MT180(180W)

## Feature:

- Mini 2 Zone Mixer Amplifier with multi audio inputs for paging & background music system.
- 2 Zone speaker output independent volume control
- Can be wall-mounted onto wall, elegant appearance and high reliable performance.
- Mini table-top design 1.5U height for commercial audio and industrial public address.
- This 2 Zone Mixer Amplifier integrate pre amplifier and power amplifier.
- Ideal for classroom, retail store, small restaurant, or office background music and paging system .
- Rated power 60W, 120W and 180W.
- 100V and low impedance  $4\Omega$ -16 $\Omega$  speaker outputs for versatile connections, with output protection cover.
- Built-in Bluetooth, USB/SD, Mp3 and FM.
- 1 Mic input (6.3mm jack), 1 AUX input by RCA on rear panel.
- One RCA AUX output on the rear panel.
- 8 knobs with individual volume control for Zone 1-2, MIC, AUX1, Mp3, bass, treble and master.
- LED indicators for power, protect and signals.
- With natural cooling fan to control internal temperature.
- Overall protection of short-circuit, overload and high temperature to avoid any damage.

## Specification:

Model	SP-MT60	SP-MT120	SP-MT180
Description	Mini 2 Zone PA Mixer Amplifier		
Rated Power	60W	120W	180W
Built-in Sources	Bluetooth, USB/SD, Mp3 & FM, 1 Mic, 1 Aux		
Speaker Output	100V & 4Ω-16Ω		
Frequency Response	80Hz~20KHz		
THD	<0.5% at 1 KHz 100V -3dB		
S/N Ratio	75dB		
Input	MIC: 6mV/1KΩ, AUX: 500mV/10KΩ		
Volume Control	Zone 1-2, MIC, AUX1, Mp3, bass, treble and master		
Tone Control	BASS: 100Hz (±10dB), TREBLE: 10kHz (±10dB)		
Cooling Method	Automatic FAN strong air cooling method		
Protection	Overheating, overload, short circuit, alarm protection		
Power Supply	AC 110~220V, 50/60Hz		
Dimension	485*88*340mm(W*H*D)		
Net Weight	5KG	6KG	8KG

## **Appearance:**





