

## **Model: SP-H30PT**

### **PA Waterproof Outdoor Horn Speaker 30W 15W 7.5W 100V 70V 8ohm with power taps**

#### **Feature:**

- Commercial PA system paging horn speaker with transformer and power taps.
- Ideal for outdoor paging and speech use in school, office, hotel and airport.
- Economy rang weatherproof horn speaker.
- Outdoor paging horn speaker for outdoor paging system.
- Superior long distance human speech clear and loud delivery.
- Rated power 3.75W / 7.5W / 15W / 30W at 100V.
- Rated power 1.8W / 3.75W / 7.5W / 15W at 70V.
- Line input 100V / 70V / 8Ω by cable tail.
- Waterproof level of IP66.
- IP66 waterproof and dust proof level.
- ABS enclosure and stainless metal bracket in white.
- Quick installation by supplied stainless mounting bracket.

#### **Specification:**

Rated Power (100V): 3.75W / 7.5W / 15W / 30W

Rated Power (70V): 1.8W / 3.75W / 7.5W / 15W

Rated Power (8Ω): 30W

Maximum Power: 45W

Input: 70V / 100V / 8Ω

Speaker Unit: 1.5"x1

Sensitivity (1W/1m): 108dB ± 3dB

Frequency Response: 300Hz-8KHz

Product Dimension: Φ285x D280mm

Weight: 2.2KG

Material: Plastic shell + iron bracket

Packing: 613\*459\*315mm, 4pcs/ctn

## **Model: SP-H30P**

### **PA Waterproof Outdoor Horn Speaker 30W 100V**

#### **Feature:**

- Commercial PA system paging horn speaker with transformer.
- Ideal for outdoor paging and speech use in school, office, hotel and airport.
- Economy rang weatherproof horn speaker.
- Outdoor paging horn speaker for outdoor paging system.
- Superior long distance human speech clear and loud delivery.
- Rated power 30W at 100V, 15W at 70V.
- Waterproof level of IP66.
- Line input 100V or 70V by cable tail.
- IP66 waterproof and dust proof level.
- ABS enclosure and stainless metal bracket in white.
- Quick installation by supplied stainless mounting bracket.

#### **Specification:**

Rated power (100V): 15W / 30W

Input: 100V

Speaker Unit: 1.5"x1

Sensitivity (1W/1m): 108dB  $\pm$  3dB

Frequency Response: 300Hz-8KHz

Product Dimension:  $\Phi$ 285x D280mm

Weight: 2KG

Material: Plastic shell + iron bracket

Packing: 613\*459\*315mm, 4pcs/ctn