

Model: SP-BW430**SURPASS Wireless blue tooth TWS amplifier wall mounting speaker for indoor outdoor home office commercial industrial pa music system**

Wireless bluetooth TWS amplifier speaker for indoor and outdoor wall mounting

Three different power:

Model: SP-BW320 (one pair) 3" active + 3" passive, size107x157x100mm, power 10W+10W

Model: SP-BW430 (one pair) 4" active + 4" passive, size125x190x115mm, power 15W+15W

Model: SP-BW540 (one pair) 5" active + 5" passive, size139x190x115mm, power 20W+20W

Function:

Bluetooth

TWS (True Wireless System) connect another active speaker without cables.

Drive two pair of 8 ohms stereo speakers.

Transmitting range up to 10 meters.

Power Supply: AC 100-240V with power adapter.

Application: HOME THEATRE, Office, Coffee shop, Portable Audio Player, Mobile Phone, Karaoke Player, COMPUTER, Stage, Others

Feature:

- Bluetooth and TWS function allows to connect to another pair speakers without cables. Extend to large scale.
- Trapeze shape allows mounting in corners at various angles, flat surface on the cabinet bottom make it possible to place the speaker on a table .
- Speaker-leads connection is very easy with 2 screw clips
- Mounting horizontally or vertically.
- The grill can be taken off.

How to operate normal bluetooth mode:

- Connect active speaker and passive speaker by speaker cable.
- Connect power adapter to active.
- Use your phone/computer to search and pair bluetooth speaker.
When pair successfully speaker will make a ring sound notice.
- Start your music apps and play music, control songs and volume on your phone computer.

How to set TWS true wireless system) mode.

- Get 2 pcs of active speaker, trun their power on.
- Press both active speakers' TWS buttons, they will make ring sound.
One active speaker will play left channel, the other play right channel sound.
Their passive speaker play the same channel as the active one.
- Use your phone/computer to pair and play.

Specification:

Model	SP-BW320	SP-BW430	SP-BW540
Rated Power	10W+10W	15W+15W	20W+20W
Frequency Range	100Hz-20KHz	90Hz-20KHz	80Hz-20KHz
SPL (@1W/m)	86dB	87dB	88dB
Woofer	3"	4"	5"
Tweeter	1/2" mylar dome	1/2" mylar dome	1/2" mylar dome
Dimension WxHxD(mm)	107x157x100mm	125x190x115mm	139x190x115mm
Colour	White or Black	White or Black	White or Black