

SP-BT64 Ceiling Speaker



Features:

▪ Rated power:4*10W/Class D digital power amplifier module; ▪ Frequency response: 120Hz-15KHz ($\pm 3\text{dB}$) ; ▪ Nonlinear distortion THD: <0.05% at 1kHz, 1/3 rated output power; ▪ Signal to noise ratio S/N: >70dB; ▪ Support blue-toothprotocol: HFPV1.5, A2DPV1.2,AVRCPV1.4, HSP1.2, GAVDP1.2, IOP; ▪ Speaker unit:Integration 6" Dual Cone Ceiling Speaker; ▪ Power consumption: 50W; ▪ Installation: Ceiling mount; ▪ Decorative materials: ABS; ▪ Power supply:AC110V~AC220V $\pm 10\%$ 50-60Hz; ▪ Case size: $\Phi 185 \times 60\text{mm}$; ▪ Opening hole size: $\Phi 170\text{mm}$; ▪ Weight: 3.5kg(4 pcs);

Specification:

| item | value |
|-----------------------------|--|
| Audio Crossover | Full-Range |
| Woofer Size/Full-Range Size | 6" |
| Communication | AUX |
| Speaker Type | In-ceiling Speaker |
| Brand Name | SURPASS |
| Model Number | BT64 |
| Type | Active |
| Use | HOME THEATRE |
| Special Feature | Wireless |
| Place of Origin | China Guangdong |
| Power consumption | 50W |
| Signal to noise ratio S/N | >70dB |
| Blue-tooth Version | 7.1 |
| Blue-tooth distance | 10m |
| Rated power | 4*10W/Class D digital power amplifier module |
| Frequency response | 120Hz-15KHz ($\pm 3\text{dB}$) |
| Speaker Unit | 6" Dual Cone Ceiling Speaker |
| Material | ABS |
| Installation Cutout Size | d170mm |
| Gross Weight | 3.5kg(4 pcs) |