

SP-AW540 Wall Mount Speaker




Features:

▪ Rated power: 20W/8Ω ▪ Input sensitivity: 0.5V ▪ Frequency Response: 80Hz-18KHz/1W, ±0.5dB ▪ Total Harmonic Distortion: 80Hz-18KHz/1W, 0.05% ▪ Damping Coefficient: >200@8Ω/400Hz ▪ Conversion Rate: 30V/US ▪ Channel Separation Degree: >75dB ▪ Signal-to-noise Ratio: >95dB ▪ Amplifier: AB class ▪ Indication: Power and Channel Signals ▪ Protection: high temperature, overload, short circuit, distortion ▪ Treble Control: ±10dB ▪ Bass Control: ±10dB ▪ Input connection: balanced Phoenix connection, dual RCA, stereo, 3.5 headphone input ▪ AC Power Supply: 220V-240V/50Hz-60Hz ▪ Speaker Unit: 5" x 1 1" x 1 ▪ Product Size: 250 x 170x 180mm ▪ Gross Weight: 6.5KGKG/pair

Specification:

item	value
Place of Origin	China
	Guangdong
Brand Name	SURPASS
Model Number	AW540
Warranty	3months-1year
Customized	Yes
Power Supply Mode	Other
Shell Material	Plastic
The body material	Plastic
Rated power	20W/8Ω
Input sensitivity	0.5V
Frequency Response	80Hz-18KHz/1W, ±0.5dB
Conversion Rate	30V/US
Damping Coefficient	>200@8Ω/400Hz
Channel Separation Degree	75dB
Indication	Power and Channel Signals
Treble Control	±10dB
Input connection	balanced Phoenix connection, dual RCA, stereo, 3.5 headphone input
Speaker Unit	5" x 1 1" x 1