

## SP-BT610 Ceiling Speaker

 Wireless Bluetooth connection



### Features:

- Frequency response: 120Hz-15KHz ( $\pm 3\text{dB}$ ) ;
- Nonlinear distortion THD:  $< 0.05\%$  at 1kHz, 1/3 rated output power;
- Signal to noise ratio S/N:  $> 70\text{dB}$ ;
- Support Blue-tooth protocol: HFPV1.5, A2DPV1.2, AVRCPV1.4, HSP1.2, GAVDP1.2, IOP;
- Speaker unit: Integration 6" Dual Cone Ceiling Speaker;
- Power consumption: 10W;
- Installation: Ceiling mount;
- Decorative materials: ABS;
- Power supply: AC110V~AC220V $\pm 10\%$  50-60Hz;
- Case size:  $\Phi 185 \times 60\text{mm}$ ;
- Opening hole size:  $\Phi 170\text{mm}$ ;
- Weight: 0.8kg(pcs) ;

### Specifications:

<b>Model Number</b>	<b>BT610</b>
<b>Use</b>	<b>HOME THEATRE, Hotel</b>
<b>Place of Origin</b>	<b>China</b>
	<b>Guangdong</b>
<b>Rated Power</b>	<b>10W</b>
<b>Frequency Response</b>	<b>120Hz-15KHz(<math>\pm 3\text{dB}</math>)</b>
<b>Nonlinear distortion THD</b>	<b><math>&lt; 0.05\%</math> at 1kHz, 1/3 rated output power</b>
<b>S/N</b>	<b><math>&gt; 70\text{dB}</math></b>
<b>Speaker Unit</b>	<b>Integration 6" Dual Cone Ceiling Speaker</b>
<b>Installation</b>	<b>Ceiling mount</b>
<b>Decorative materials</b>	<b>ABS</b>
<b>Power supply</b>	<b>AC110V~AC220V<math>\pm 10\%</math> 50-60Hz</b>
<b>Case size</b>	<b>d185x60mm</b>
<b>Weight</b>	<b>0.8kg(pcs)</b>